



Categoria / Category

Incassi / Downlights

IP20



220/240V  
50/60 Hz

RG1



Ta  
35°

### Specifiche meccaniche / Mechanical specs

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Riflettore in Alluminio / Aluminum Reflector

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Foro incasso / Cutting hole

Ø105 mm

### Specifiche elettriche / Electrical specs

Alimentatore / Driver

Incluso / Included

Regolazione / Diming

Dimmerabile DALI / DALI Dimmable

Tensione in ingresso / Input voltage

220-240V / 50-60Hz

Potenza sistema / System power

13,5 W

Potenza sorgente / Source power

12 W

Corrente di Alimentazione / Supply current

350 mA

Efficienza / Efficiency

91 lm/W

Classe energetica / Energy efficiency class

G

Specifiche illuminotecniche / *Illuminotecnical specs*

Sorgente / <i>Light source</i>	COB - LES15
SDCM	3
IRC / <i>CRI</i>	>90
Temperatura colore / <i>CCT</i>	Bread K
Flusso nom. / <i>Nom. flux</i>	1100 lm
Flusso effettivo / <i>Effective flux</i>	875 lm
LOR	80%
Durata LED / <i>LED lifetime</i>	L80B20 (@50000hr)
Fascio / <i>Beam</i>	30°



Accessori / *Accessories*

**Kit di Emergenza Remoto**  
*Remoted Emergency Kit*



123010

**Kit di Emergenza Remoto**  
*Remoted Emergency Kit*



123023-3

**Filtro Opale**  
*Opal Filter*



0796000U