



Categoria / Category

Incassi / Downlights

IP20



220/240V  
50/60 Hz

RG1



Ta  
35°

### Specifiche meccaniche / Mechanical specs

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Riflettore in Alluminio / Aluminum Reflector

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Foro incasso / Cutting hole

Ø105 mm

### Specifiche elettriche / Electrical specs

Alimentatore / Driver

Incluso / Included

Regolazione / Diming

Dimmerabile Push / Push Dimmable

Tensione in ingresso / Input voltage

220-240V / 50-60Hz

Potenza sistema / System power

19,5 W

Potenza sorgente / Source power

17 W

Corrente di Alimentazione / Supply current

500 mA

Efficienza / Efficiency

90 lm/W

Classe energetica / Energy efficiency class

G

**Specifiche illuminotecniche / Illuminotecnical specs**


---


Sorgente / Light source	COB - LES15
SDCM	3
IRC / CRI	>90
Temperatura colore / CCT	Bread K
Flusso nom. / Nom. flux	1530 lm
Flusso effettivo / Effective flux	1217 lm
LOR	80%
Durata LED / LED lifetime	L80B20 (@50000hr)
Fascio / Beam	30°


**Accessori / Accessories**


---

**Kit di Emergenza Remoto**  
*Remoted Emergency Kit*

**123010**
**Kit di Emergenza Remoto**  
*Remoted Emergency Kit*

**123023-3**
**Filtro Opale**  
*Opal Filter*

**0796000U**