



Categoria / Category

Incassi / Downlights



Specifiche meccaniche / Mechanical specs

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Riflettore in Alluminio / Aluminum Reflector

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Foro incasso / Cutting hole

Ø105 mm

Specifiche elettriche / Electrical specs

Alimentatore / Driver

Non incluso / Not Included

Tensione in ingresso / Input voltage

36V CC

Potenza sorgente / Source power

21 W

Corrente di Alimentazione / Supply current

600 mA

Efficienza / Efficiency

86 lm/W

Classe energetica / Energy efficiency class

G


Specifiche illuminotecniche / Illuminotecnical specs

Sorgente / <i>Light source</i>	COB - LES15
SDCM	3
IRC / <i>CRI</i>	>90
Temperatura colore / <i>CCT</i>	Bread K
Flusso nom. / <i>Nom. flux</i>	1810 lm
Flusso effettivo / <i>Effective flux</i>	1440 lm
LOR	80%
Durata LED / <i>LED lifetime</i>	L80B20 (@50000hr)
Fascio / <i>Beam</i>	15°


Accessori / Accessories

Kit di Emergenza Remoto
Remoted Emergency Kit

123010
Kit di Emergenza Remoto
Remoted Emergency Kit

123023-3
Filtro Opale
Opal Filter

0796000U