



Categoria / Category

Incassi / Downlights

IP20



220/240V
50/60 Hz

RG1



Ta
35°

Specifiche meccaniche / Mechanical specs

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Riflettore in Alluminio / Aluminum Reflector

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Foro incasso / Cutting hole

Ø105 mm

Specifiche elettriche / Electrical specs

Alimentatore / Driver

Incluso / Included

Regolazione / Diming

Non Dimmerabile / Not Dimmable

Tensione in ingresso / Input voltage

220-240V / 50-60Hz

Potenza sistema / System power

24 W

Potenza sorgente / Source power

21 W

Corrente di Alimentazione / Supply current

600 mA

Efficienza / Efficiency

86 lm/W

Classe energetica / Energy efficiency class

G

Specifiche illuminotecniche / Illuminotecnical specs

Sorgente / Light source	COB - LES15
SDCM	3
IRC / CRI	>90
Temperatura colore / CCT	Bread K
Flusso nom. / Nom. flux	1810 lm
Flusso effettivo / Effective flux	1440 lm
LOR	80%
Durata LED / LED lifetime	L80B20 (@50000hr)
Fascio / Beam	30°



Accessori / Accessories

Kit di Emergenza Remoto
Remoted Emergency Kit



123010

Kit di Emergenza Remoto
Remoted Emergency Kit



123023-3

Filtro Opale
Opal Filter



0796000U