



Categoria / Category

Incassi / Downlights

IP20

220/240 V  
50/60 Hz

RG1

CE

Ta  
35°

Specifiche meccaniche / Mechanical specs

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| Corpo / Body                | Pressofusione di Alluminio / Die-Cast Aluminium Body |
| Ottica / Optic              | Riflettore in Alluminio / Aluminium Reflector        |
| Verniciatura / Finishing    | Verniciatura a Polvere / Powder Painted              |
| Foro incasso / Cutting hole | Ø105 mm                                              |

Specifiche elettriche / Electrical specs

|                                            |                                        |
|--------------------------------------------|----------------------------------------|
| Alimentatore / Driver                      | Incluso / Included                     |
| Regolazione / Diming                       | Dimmerabile Casambi / Casambi Dimmable |
| Tensione in ingresso / Input voltage       | 220-240V / 50-60Hz                     |
| Potenza sistema / System power             | 13,5 W                                 |
| Potenza sorgente / Source power            | 12 W                                   |
| Corrente di Alimentazione / Supply current | 350 mA                                 |
| Efficienza / Efficiency                    | 87 lm/W                                |

Specifiche illuminotecniche / *Illuminotecnical specs*

|                                          |                   |
|------------------------------------------|-------------------|
| Sorgente / <i>Light source</i>           | COB - LES15       |
| SDCM                                     | 3                 |
| IRC / <i>CRI</i>                         | >90               |
| Temperatura colore / <i>CCT</i>          | Meat K            |
| Flusso nom. / <i>Nom. flux</i>           | 1050 lm           |
| Flusso effettivo / <i>Effective flux</i> | 835 lm            |
| LOR                                      | 80%               |
| Durata LED / <i>LED lifetime</i>         | L80B20 (@50000hr) |
| Fascio / <i>Beam</i>                     | 15°               |



Accessori / *Accessories*

Kit di Emergenza Remoto  
*Remoted Emergency Kit*



123010

Kit di Emergenza Remoto  
*Remoted Emergency Kit*



123023-3

Filtro Opale  
*Opal Filter*



0796000U