**Categoria / Category****Incassi / Downlights**

IP20

mA

RG1

Ta
35°**Specifiche meccaniche / Mechanical specs****Corpo / Body**

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Riflettore in Alluminio / Aluminum Reflector

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Foro incasso / Cutting hole

Ø105 mm

Specifiche elettriche / Electrical specs**Alimentatore / Driver**

Non Incluso / Not Included

Tensione in ingresso / Input voltage

36V CC

Potenza sorgente / Source power

21 W

Corrente di Alimentazione / Supply current

600 mA

Efficienza / Efficiency


82 lm/W

Specifiche illuminotecniche / Illuminotecnical specs


Sorgente / Light source	COB - LES15
SDCM	3
IRC / CRI	>90
Temperatura colore / CCT	Meat K
Flusso nom. / Nom. flux	1730 lm
Flusso effettivo / Effective flux	1376 lm
LOR	80%
Durata LED / LED lifetime	L80B20 (@50000hr)
Fascio / Beam	50°

**Accessori / Accessories****Kit di Emergenza Remoto**
Remoted Emergency Kit

123010

Kit di Emergenza Remoto
Remoted Emergency Kit

123023-3

Filtro Opale
Opal Filter

0796000U