



Categoria / Category

Incassi / Downlights



**Specifiche meccaniche / Mechanical specs**

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Riflettore in Alluminio / Aluminum Reflector

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Foro incasso / Cutting hole

Ø105 mm

**Specifiche elettriche / Electrical specs**

Alimentatore / Driver

Non incluso / Not Included

Tensione in ingresso / Input voltage

36V CC

Potenza sorgente / Source power

17 W

Corrente di Alimentazione / Supply current

500 mA

Efficienza / Efficiency

140 lm/W

Classe energetica / Energy efficiency class

E

**Specifiche illuminotecniche / Illuminotecnical specs**


---


Sorgente / <i>Light source</i>	COB - LES15
SDCM	3
IRC / <i>CRI</i>	>90
Temperatura colore / <i>CCT</i>	3000 K
Flusso nom. / <i>Nom. flux</i>	2390 lm
Flusso effettivo / <i>Effective flux</i>	1901 lm
LOR	80%
Durata LED / <i>LED lifetime</i>	L80B20 (@50000hr)
Fascio / <i>Beam</i>	30°


**Accessori / Accessories**


---

**Kit di Emergenza Remoto**  
*Remoted Emergency Kit*

**123010**
**Kit di Emergenza Remoto**  
*Remoted Emergency Kit*

**123023-3**
**Filtro Opale**  
*Opal Filter*

**0796000U**