



Hammer Mini
Art. 0796TQC1



Categoria / Category

Incassi / Downlights

IP20

mA

RG1

Ta
35°

Specifiche meccaniche / Mechanical specs

Corpo / Body

Ottica / Optic

Verniciatura / Finishing

Foro incasso / Cutting hole

Pressofusione di Alluminio / Die-Cast Aluminium Body

Riflettore in Alluminio / Aluminum Reflector

Verniciatura a Polvere / Powder Painted

Ø105 mm

Specifiche elettriche / Electrical specs

Alimentatore / Driver

Tensione in ingresso / Input voltage

Potenza sorgente / Source power

Corrente di Alimentazione / Supply current

Efficienza / Efficiency

Classe energetica / Energy efficiency class

Non Incluso / Not Included

36V CC

21 W

600 mA

141 lm/W

E


Specifiche illuminotecniche / *Illuminotecnical specs*

Sorgente / <i>Light source</i>	COB - LES15
SDCM	3
IRC / <i>CRI</i>	>90
Temperatura colore / <i>CCT</i>	4000 K
Flusso nom. / <i>Nom. flux</i>	2980 lm
Flusso effettivo / <i>Effective flux</i>	2371 lm
LOR	80%
Durata LED / <i>LED lifetime</i>	L80B20 (@50000hr)
Fascio / <i>Beam</i>	15°




Accessori / *Accessories*

Kit di Emergenza Remoto
Remoted Emergency Kit



123010

Kit di Emergenza Remoto
Remoted Emergency Kit



123023-3

Filtro Opale
Opal Filter



0796000U