**Categoria / Category****Incassi / Downlights**

IP40

220/240 V  
50/60 Hz

RG1

Ta  
35°**Specifiche meccaniche / Mechanical specs****Corpo / Body**

Pressofusione di Alluminio / Die-Cast Aluminium Body

**Ottica / Optic**

Lente TIR in PMMA / PMMA TIR Lens

**Verniciatura / Finishing**

Verniciatura a Polvere / Powder Painted

**Peso / Weight**

0,1 kg

**Foro incasso / Cutting hole**

Ø25 mm

**Specifiche elettriche / Electrical specs****Alimentatore / Driver**

Incluso / Incluso

**Regolazione / Diming**

Dimmerabile Push / Push Dimmable

**Tensione in ingresso / Input voltage**

220-240V / 50-60Hz

**Potenza sistema / System power**

2 W

**Potenza sorgente / Source power**

1,5 W

**Corrente di Alimentazione / Supply current**

500 mA

**Efficienza / Efficiency**

91 lm/W

**Classe energetica / Energy efficiency class**

F

**Specifiche illuminotecniche / Illuminotecnical specs**

<b>Sorgente / Light source</b>	Scheda LED Custom
<b>SDCM</b>	3
<b>IRC / CRI</b>	>90
<b>Temperatura colore / CCT</b>	3000 K
<b>Flusso nom. / Nom. flux</b>	137 lm
<b>Flusso effettivo / Effective flux</b>	112 lm
<b>LOR</b>	82%
<b>Durata LED / LED lifetime</b>	L80B20 (@50000hr)
<b>Fascio / Beam</b>	15°


**Accessori / Accessories**

**Alimentatore On-Off / Push per Collegamenti in Serie (2 - 11 pz)**  
*On-Off / Push Driver for In Series Connection (2 - 11 pcs)*



125400

**Alimentatore Casambi per Collegamenti in Serie (2 - 11 pz)**  
*Casambi Driver for In Series Connection (2 - 11 pcs)*



127630

**Alimentatore DALI per Collegamenti in Serie (2 - 11 pz)**  
*DALI Driver for In Series Connection (2 - 11 pcs)*



151403