




Categoria / Category

Incassi / Downlights

IP40

220/240 V  
50/60 Hz

RG1

Ta  
35°

Specifiche meccaniche / Mechanical specs

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| Corpo / Body                | Pressofusione di Alluminio / Die-Cast Aluminium Body |
| Ottica / Optic              | Lente TIR in PMMA / PMMA TIR Lens                    |
| Verniciatura / Finishing    | Verniciatura a Polvere / Powder Painted              |
| Peso / Weight               | 0,1 kg                                               |
| Foro incasso / Cutting hole | Ø25 mm                                               |

Specifiche elettriche / Electrical specs

|                                             |                                  |
|---------------------------------------------|----------------------------------|
| Alimentatore / Driver                       | Incluso / Includo                |
| Regolazione / Diming                        | Dimmerabile DALI / DALI Dimmable |
| Tensione in ingresso / Input voltage        | 220-240V / 50-60Hz               |
| Potenza sistema / System power              | 2 W                              |
| Potenza sorgente / Source power             | 1,5 W                            |
| Corrente di Alimentazione / Supply current  | 500 mA                           |
| Efficienza / Efficiency                     | 91 lm/W                          |
| Classe energetica / Energy efficiency class | F                                |

Specifiche illuminotecniche / *Illuminotecnical specs*

|                                          |                   |
|------------------------------------------|-------------------|
| Sorgente / <i>Light source</i>           | Scheda LED Custom |
| SDCM                                     | 3                 |
| IRC / <i>CRI</i>                         | >90               |
| Temperatura colore / <i>CCT</i>          | 3000 K            |
| Flusso nom. / <i>Nom. flux</i>           | 137 lm            |
| Flusso effettivo / <i>Effective flux</i> | 112 lm            |
| LOR                                      | 82%               |
| Durata LED / <i>LED lifetime</i>         | L80B20 (@50000hr) |
| Fascio / <i>Beam</i>                     | 45°               |



Accessori / *Accessories*

Alimentatore On-Off / Push  
per Collegamenti in Serie (2 -  
11 pz)  
*On-Off / Push Driver for In  
Series Connection (2 - 11 pcs)*



125400

Alimentatore Casambi per  
Collegamenti in Serie (2 - 11  
pz)  
*Casambi Driver for In Series  
Connection (2 - 11 pcs)*



127630

Alimentatore DALI per  
Collegamenti in Serie (2 - 11  
pz)  
*DALI Driver for In Series  
Connection (2 - 11 pcs)*



151403