

Categoria / Category

Incassi / Downlights

IP40



220/240V  
50/60 Hz

RG1



Ta  
35°

### Specifiche meccaniche / Mechanical specs

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Lente TIR in PMMA / PMMA TIR Lens

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Peso / Weight

0,1 kg

Foro incasso / Cutting hole

Ø25 mm

### Specifiche elettriche / Electrical specs

Alimentatore / Driver

Incluso / Includo

Regolazione / Diming

Non Dimmerabile / Not Dimmable

Tensione in ingresso / Input voltage

220-240V / 50-60Hz

Potenza sistema / System power

2 W

Potenza sorgente / Source power

1,5 W

Corrente di Alimentazione / Supply current

500 mA

Efficienza / Efficiency

96 lm/W

Classe energetica / Energy efficiency class

F


**Specifiche illuminotecniche / Illuminotecnical specs**

Sorgente / Light source	Scheda LED Custom
SDCM	3
IRC / CRI	>90
Temperatura colore / CCT	4000 K
Flusso nom. / Nom. flux	144 lm
Flusso effettivo / Effective flux	117 lm
LOR	82%
Durata LED / LED lifetime	L80B20 (@50000hr)
Fascio / Beam	24°


**Accessori / Accessories**

**Alimentatore On-Off / Push per Collegamenti in Serie (2 - 11 pz)**


*On-Off / Push Driver for In Series Connection (2 - 11 pcs)*



125400

**Alimentatore Casambi per Collegamenti in Serie (2 - 11 pz)**

*Casambi Driver for In Series Connection (2 - 11 pcs)*



127630

**Alimentatore DALI per Collegamenti in Serie (2 - 11 pz)**

*DALI Driver for In Series Connection (2 - 11 pcs)*



151403