**Categoria / Category****Incassi / Downlights**

IP40

220/240 V
50/60 Hz

RG1

Ta
35°**Specifiche meccaniche / Mechanical specs****Corpo / Body**

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Lente TIR in PMMA / PMMA TIR Lens

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Peso / Weight

0,1 kg

Foro incasso / Cutting hole

Ø25 mm

Specifiche elettriche / Electrical specs**Alimentatore / Driver**

Incluso / Incluso

Regolazione / Diming

Dimmerabile Push / Push Dimmable

Tensione in ingresso / Input voltage

220-240V / 50-60Hz

Potenza sistema / System power

2 W

Potenza sorgente / Source power

1,5 W

Corrente di Alimentazione / Supply current

500 mA

Efficienza / Efficiency

96 lm/W

Classe energetica / Energy efficiency class

F

Specifiche illuminotecniche / Illuminotecnical specs

| | |
|--|-------------------|
| Sorgente / Light source | Scheda LED Custom |
| SDCM | 3 |
| IRC / CRI | >90 |
| Temperatura colore / CCT | 4000 K |
| Flusso nom. / Nom. flux | 144 lm |
| Flusso effettivo / Effective flux | 117 lm |
| LOR | 82% |
| Durata LED / LED lifetime | L80B20 (@50000hr) |
| Fascio / Beam | 45° |

**Accessori / Accessories**

Alimentatore On-Off / Push per Collegamenti in Serie (2 - 11 pz)
On-Off / Push Driver for In Series Connection (2 - 11 pcs)




125400

Alimentatore Casambi per Collegamenti in Serie (2 - 11 pz)
Casambi Driver for In Series Connection (2 - 11 pcs)



127630

Alimentatore DALI per Collegamenti in Serie (2 - 11 pz)
DALI Driver for In Series Connection (2 - 11 pcs)



151403