**Categoria / Category****Incassi / Downlights**

IP40

mA

RG1

Ta
35°**Specifiche meccaniche / Mechanical specs****Corpo / Body**

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Lente TIR in PMMA / PMMA TIR Lens

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Peso / Weight

0,1 kg

Foro incasso / Cutting hole

Ø25 mm

Specifiche elettriche / Electrical specs**Alimentatore / Driver**

Non Incluso / Not Included

Tensione in ingresso / Input voltage

3V CC

Potenza sorgente / Source power

1,5 W

Corrente di Alimentazione / Supply current

500 mA

Efficienza / Efficiency

86 lm/W

Classe energetica / Energy efficiency class

F

Specifiche illuminotecniche / Illuminotechnical specs

Sorgente / Light source	Scheda LED Custom
SDCM	3
IRC / CRI	>90
Temperatura colore / CCT	2700 K
Flusso nom. / Nom. flux	130 lm
Flusso effettivo / Effective flux	106 lm
LOR	82%
Durata LED / LED lifetime	L80B20 (@50000hr)
Fascio / Beam	24°


**Accessori / Accessories**

Alimentatore On-Off / Push per Collegamenti in Serie (2 - 11 pz)
On-Off / Push Driver for In Series Connection (2 - 11 pcs)



125400

Alimentatore Casambi per Collegamenti in Serie (2 - 11 pz)
Casambi Driver for In Series Connection (2 - 11 pcs)



127630

Alimentatore DALI per Collegamenti in Serie (2 - 11 pz)
DALI Driver for In Series Connection (2 - 11 pcs)



151403