

Categoria / Category

Incassi / Downlights

IP40



220/240V
50/60 Hz

RG1



Ta
35°

Specifiche meccaniche / Mechanical specs

Corpo / Body

Pressofusione di Alluminio / Die-Cast Aluminium Body

Ottica / Optic

Lente TIR in PMMA / PMMA TIR Lens

Verniciatura / Finishing

Verniciatura a Polvere / Powder Painted

Peso / Weight

0,1 kg

Foro incasso / Cutting hole

Ø25 mm

Specifiche elettriche / Electrical specs

Alimentatore / Driver

Incluso / Includo

Regolazione / Diming

Non Dimmerabile / Not Dimmable

Tensione in ingresso / Input voltage

220-240V / 50-60Hz

Potenza sistema / System power

2 W

Potenza sorgente / Source power

1,5 W

Corrente di Alimentazione / Supply current

500 mA

Efficienza / Efficiency

86 lm/W

Classe energetica / Energy efficiency class

F

Specifiche illuminotecniche / *Illuminotecnical specs*


| | |
|--|-------------------|
| Sorgente / <i>Light source</i> | Scheda LED Custom |
| SDCM | 3 |
| IRC / <i>CRI</i> | >90 |
| Temperatura colore / <i>CCT</i> | 2700 K |
| Flusso nom. / <i>Nom. flux</i> | 130 lm |
| Flusso effettivo / <i>Effective flux</i> | 106 lm |
| LOR | 82% |
| Durata LED / <i>LED lifetime</i> | L80B20 (@50000hr) |
| Fascio / <i>Beam</i> | 24° |



Accessori / *Accessories*

Alimentatore On-Off / Push per Collegamenti in Serie (2 - 11 pz)


On-Off / Push Driver for In Series Connection (2 - 11 pcs)



125400

Alimentatore Casambi per Collegamenti in Serie (2 - 11 pz)

Casambi Driver for In Series Connection (2 - 11 pcs)



127630

Alimentatore DALI per Collegamenti in Serie (2 - 11 pz)

DALI Driver for In Series Connection (2 - 11 pcs)



151403